CB-HD39N-L



KEY FEATURES

- 1/3" CCD Sensor
- 600 TV Lines (Color), 650 TV Lines (B/W)
- 2.8~11mm, DC Auto Iris Lens
- · Day/Night Functionality with ICR
- 0.2 Lux (Color), 0.00 Lux (B/W, IR LEDs On)
- 24 IR LEDs (Up to 50ft.)
- Smart IR Automatic Intensity Adjustment
- IR LED On/Off Switch
- 0.2 Lux (Color), 0.00 Lux (B/W, IR LEDs On)
- DNR: Digital Noise Reduction
- ATW: Automatic Tracking White Balance
- HLC: High Light Compensation
- DWDR: Digital Wide Dynamic Range
- Service Monitor Output
- 12VDC/24VAC Dual Voltage

CONSTRUCTION

- 3-Axis Bracket (Wire Feed-through)
- Weatherproof Aluminum Housing

AVAILABLE ACCESSORIES

CA-ORC: Service Monitor and OSD Controller Cable

TECHNICAL SPECIFICATIONS

Technical Specifications	CB-HD39N-L
Video Format	NTSC
Image Sensor	1/3" CCD
Horizontal Resolution	600 TV Lines (Color), 650 TV Lines (B/W)
Day/Night Functionality	Yes w/ ICR
Lens Type (DC Auto Iris)	Vari-focal 2.8mm-11mm
Angle of View	134°(W) ~ 36°(T)
IR LEDs	24
IR LEDs Distance	Up to 50ft.
LEDs Illumination Angle	80°
Sync System	Internal
Effective Pixels (HxV)	768(H) x 494(V)
Scanning System	525 Lines. 2:1 Interlaced
Electronic Shutter	1/60 sec.
Main Video Output	1.0 Vp-p Composite, 75 ohm
Service Monitor Output	1.0 Vp-p Composite, 75 ohm
Minimum Illumination	0.2 Lux (Color), 0.00 Lux (B/W, IR LED On)
S/N Ratio	More than 48dB (AGC Off)
Camera Control & Setup	OSD Menu
General Information	CB-HD39N-L
Operating Temperature	23°F ~ 113°F (-5°C ~ +45°C)
Operating Humidity	Within 90% RH
Power Consumption	14W / 1 Amp (LEDs On), 4W / 500mA (Camera Only)
Input Voltage	12VDC / 24VAC Dual Voltage

*Specifications are subject to change without any prior notice.

CLEARLY BETTER.



3-Axis Bracket with Wire Feed-through

Much more than a clean, neat installation, this fully functional 3-axis bracket is also a wire feed-through bracket which secures your camera cables within the aluminum metal housing preventing unwanted vandalism and interruption to your video feed. And now, twice as sturdy!



Smart IR LEDs Has Got You Covered

Tired of "hotspots" or too much IR reflection? Our new bullet camera has got you covered - Smart IR LEDs.

All our bullet cameras come equipped with Smart IR LED technology that detects too much IR reflection and automatically compensates. Smart.

DIMENSIONS

Unit: Inches (mm)

